

Z509-TX2 NX

User Manual

Realtimes Beijing Technology Co., LTD.

Fax: +86 010-84284669 / 84280996

Email: info@realtimes.cn

Web Page: <https://www.realtimesai.com>

Address: 11th Floor, Block B, 20th Heping Xiyuan, Pingxi Street, Chaoyang District, Beijing 100013, P.R.China



Revision History

Revision	Date	Reason for change	Applicable hardware version
V1.0	2021-03	Initial release	V2.0



Electronic components and circuits are very sensitive to electrostatic discharge. Although our company designs anti-static protection for the main interfaces on the card when designing circuit board products, it is difficult to achieve anti-static safety protection for all components and circuits. Therefore, it is recommended to observe anti-static safety precautions when handling any circuit board component (including Z509-TX2 NX). Anti-static safety protection measures include, but are not limited to the following:

- a) The smart box should be placed in an anti-static bag during transportation and storage, and then the board should not be taken out during installation and deployment.
- b) Before touching the smart box, discharge the static electricity stored in the body: wear a discharge grounding wrist strap.
- c) Operate the smart box only within the safe area of the electrostatic discharge point.
- d) Avoid moving smart boxes in carpeted areas.

Precautions and after-sales maintenance

matters needing attention

Before using the product, please read this manual carefully and keep it for future reference;

- Please pay attention to and follow all warning and guidance information marked on the product;
- Please use matching power adapter to ensure the stability of voltage and current;
- Please use this product in a cool, dry and clean place;
- Do not use this product in cold and hot alternate environment to avoid condensation damage components;
- Do not splash any liquid on the product. Do not use organic solvent or corrosive liquid to clean the product;
- Do not use the product in dusty and messy environment. If it is not used for a long time, please pack the product;
- Do not use in the environment with excessive vibration, any dropping or knocking may damage the circuit and components;
- Do not plug and unplug the core board and peripheral modules when power is on;
- Please do not repair or disassemble the product by yourself. In case of any fault, please contact



our company in time for maintenance;

- Do not modify or use unauthorized accessories by yourself, and the damage caused will not be warranted;

After sales maintenance

1) Warranty period

- Base plate, core plate : 3 year (non-human damage)
- Other peripherals sold by the company: 1 year (non-human damage)

2) Warranty description

- Within 7 days: the product (base plate, core module) is not damaged by human, our company will replace / repair it free of charge, and bear the return freight; (because the core module needs NVIDIA to confirm that it can meet the requirements of repair, it will take a long time, we will coordinate as soon as possible, please forgive for the inconvenience)

- From 7 days to 36 months: the product (base plate, core module) is not damaged by human, our company will repair it free of charge, and bear the return freight; (because the core module needs NVIDIA to confirm that it can meet the requirements of repair, it will take a long time, we will coordinate as soon as possible, please forgive for the inconvenience)

- Artificial damage in more than 3 year or 3 year: the product (carrier plate) shall be tested after it is sent to the customer, and the customer shall be informed of whether it can be repaired and the maintenance cost in detail. After reaching an agreement, the product shall be repaired and returned to the customer, and the company shall bear the return freight;

- The starting time shall be subject to the date of express delivery receipt;

3) Contact information

Official website: www.realtimesai.com

Taobao website: <https://shop340963258.taobao.com/>

Address: 11, block B, Heping Xiyuan, Heping West Street, Chaoyang District, Beijing

Attention: RMA

Tel: 010-84284669

Mailing notice: contact with the company's sales department in advance, arrange technical support personnel to check and eliminate errors caused by misoperation as soon as possible, fill in the product after-sale return to factory maintenance form after verification, and send it to rma@realtimes.cn Mail box, please attach the list of items to facilitate verification, so as to avoid loss and loss in the process of express delivery. The company does not receive any delivery

Technical support and development customization

1. Scope of technical support

- 1) The company releases the electrical characteristics and use of industrial carrier boards and modules;
- 2) Physical dimension of hardware, relevant structure diagram and line sequence definition of specific interface;
- 3) Burn in verification of all BSP support packages provided by the company;
- 4) The company released burn environment construction, entry-level use. ;
- 5) Various peripheral module drivers released by the company;
- 6) The company's product fault diagnosis and after-sales maintenance services;

2. Scope of technical discussion



Table of Contents

1 PRODUCT INTRODUCTION..... 6

 1.1 FEATURES..... 6

 1.2 ORDERING INFORMATION..... 7

2 EXTERNAL INTERFACE FUNCTION AND LOCATION..... 8

3 INSTALLATION AND USE..... 9

 3.1 HOW TO USE SMART BOX..... 9

 3.2 RECOVERY MODE..... 9

4 CONNECTORS DESCRIPTION..... 10

 4.1 MINI HDMI INTERFACE..... 10

 4.2 ETHERNET CONNECTOR..... 10

 4.3 USB3.0 INTERFACE..... 10

 4.4 SD CARD SLOT..... 10

 4.5 POWER INPUT PORT..... 11

 4.6 OTG-USB2.0 INTERFACE..... 11

 4.7 MULTI-FUNCTION CONNECTOR..... 11

 4.8 WIFI ANTENNA CONNECTOR..... 12

5 HARDWARE UPDATE HISTORY..... 12

6 PRODUCT SIZE DIAGRAM..... 12

7 SOFTWARE/BSP DETAILS..... 13

TERMS OF WARRANTY..... 14

1 Product introduction

Z509-TX2 NX is a new Feiyun Smart Box™ based on NVIDIA Jetson™ TX2 NX series module design, built-in TX2 NX module integrated with 256-core NVIDIA Pascal™ architecture GPU, pre-installed Ubuntu 18.04 operating system, with 1.33TOPS floating point AI processing capabilities for computing. It adopts super strong and lightweight aluminum alloy material design, conductive heat dissipation, excellent heat dissipation capacity, small and light overall size, reserved side wing structure for easy on-site installation, and 7x24-hour long MTBF stable operation capability on site. It can be applied to robots, Autonomous machines such as unmanned delivery vehicles, smart gates, and smart vending cabinets are ideal carriers for deploying AI computing power at the edge for deep learning.

1.1 Features

Compatible with nvidia Jetson TX2 NX module

GPU: NVIDIA Jetson™ TX2 NX with 256-core NVIDIA Pascal architecture

CPU: Dual-core NVIDIA Denver 2 64-bit CPU and quad-core ARM A57 Complex

Operating system:Ubuntu18.04

Memory: 4GB LPDDR4

Storage: Built-in 16GB or expandable TF card slot

- 1 x USB3.0, 1 x USB2.0, 1 x USB2.0 OTG
- 1 x Mini HDMI
- 1 x GbE (10/100/1000 BASE-T)
- 2 x MIPI Camera interface
- 1 x Mini-PCIE
- 1 x Micro SD Card slot
- 1 x UART/I2C interface
- 1 x Button interface
- Dimensions: 109.1mm×77mm×46mm
- Cooling method:Conductive heat dissipation (no fan)
- Power Requirements: +12V
- Environmental: -20℃--+55℃
- Weight: 406g

1.2 Ordering Information

Model Options	Functional Description
Z509-TX2 NX	Z509-TX2 NX Feiyun Smart Box Conductive Cooling Edition (V2.0), built-in TX2 NX module, pre-installed Ubuntu 18.04, built-in 16GB eMMC; 1 x USB 3.0, 1 x USB 2.0, 1 x USB OTG, 1 x miniHDMI, 1 x GbE, 2 x MIPI CSI-2/2 Lane, 1x Micro SD, 3x 3.3V UART, 2 x SPI, 2 x I2C, 1 x MiniPCIe, 4G module optional; power indicator, power switch button, -20 — +55 °C ; including cable package (HDMI, serial port, SPI, I2C); including power adapter, providing Ruitai new era RTS-Linux4Tegra software support package
RTSV-6911i (Optional) RTSV-6901 (Optional) RTSV-6941 (Optional)	Mini-PCIe video capture card, RTSV-6911i (8 channel D1 NTSC/PAL video input), RTSV-6901 (single channel SDI video input), RTSV-6941 (single channel HDMI video input)
ME909S-821 (Optional)	mini-PCIe full Netcom 4G module

Order online:

<https://shop340963258.taobao.com>

<https://mall.jd.com/index-824786.html>

2 External interface function and location



Z509-TX2 NX Front



Z509-TX2 NX Back

3 Installation and use

3.1 How to use Smart Box

- a) Ensure that the voltage of all external systems is turned off
- b) Install necessary external cables. (Such as: the display cable connected to the HDMI display, the power input cable to power the system, the USB cable connecting the keyboard and mouse ...)
- c) Connect the power cord to a power source.
- d) Z509-TX2 NX adopts automatic power-on design. Turn on the power and the system starts to work.

3.2 Recovery Mode


Jetson TX2 NX core module can work in normal mode and Recovery mode. File system update, kernel update, boot loader update, BCT update and other operations can be performed in Recovery mode.

The steps to enter Recovery mode are as follows:


- a) Turn off the system power supply.
- b) Use a USB cable to connect the OTG-USB port of Z509-TX2 NX and the USB port of the Jetson development host.
- c) Short-circuit pins 1 and 9 of the Button connector to supply power to the system. Keep the power supply for more than 3 seconds, and then disconnect the short wires of pins 1 and 9 of the Button connector.
- d) The system enters Recovery mode, and subsequent operations can be performed at this time.

4 Connectors Description


4.1 Mini HDMI interface

Function	HDMI interface	
Marking	HDMI	
Type	Mini HDMI connector	


4.2 Ethernet connector

Function	Gigabit Ethernet connector	
Marking	ETH	
Type	RJ45	


4.3 USB3.0 interface

Function	USB3.0 interface	
Marking	USB3.0	
Type	Type-A The upper layer is USB2.0 interface The lower layer is USB3.0 interface	


4.4 SD Card slot

Function	SD Card slot	
Marking	TF card	
Type	Micro SD (TF)	


4.5 Power input port


Function	Power input port	
Marking	12V	
Type	2Pin interface	

4.6 OTG-USB2.0 interface


Function	USB2.0 (OTG)	
Marking	OGT	
Type	UBS2.0 Micro Type-B	

4.7 Multi-function connector

Function	Serial port																											
Marking	UART																											
Type	DB9																											
Function	<table border="1"> <thead> <tr> <th>Pin</th> <th>Signal</th> <th>Pin</th> <th>Signal</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>UART2_TXD</td> <td>2</td> <td>UART2_RTS</td> </tr> <tr> <td>3</td> <td>UART3_TXD</td> <td>4</td> <td>UART3_RTS</td> </tr> <tr> <td>5</td> <td>GND</td> <td>6</td> <td>UART2_RXD</td> </tr> <tr> <td>7</td> <td>UART2_CTS</td> <td>8</td> <td>UART3_RXD</td> </tr> <tr> <td>9</td> <td>UART3_CTS</td> <td></td> <td></td> </tr> </tbody> </table>	Pin	Signal	Pin	Signal	1	UART2_TXD	2	UART2_RTS	3	UART3_TXD	4	UART3_RTS	5	GND	6	UART2_RXD	7	UART2_CTS	8	UART3_RXD	9	UART3_CTS					
Pin	Signal	Pin	Signal																									
1	UART2_TXD	2	UART2_RTS																									
3	UART3_TXD	4	UART3_RTS																									
5	GND	6	UART2_RXD																									
7	UART2_CTS	8	UART3_RXD																									
9	UART3_CTS																											

Function	Multi-function pin																											
Marking	Button																											
Type	DB9																											
Function	<table border="1"> <thead> <tr> <th>Pin</th> <th>Signal</th> <th>Pin</th> <th>Signal</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>GND</td> <td>2</td> <td>GND</td> </tr> <tr> <td>3</td> <td>GND</td> <td>4</td> <td>GND</td> </tr> <tr> <td>5</td> <td>GND</td> <td>6</td> <td>DEV_3V3</td> </tr> <tr> <td>7</td> <td>DEV_3V3</td> <td>8</td> <td>BUTTON_PWR_ON</td> </tr> <tr> <td>9</td> <td>FORCE_RECOVER Y</td> <td></td> <td></td> </tr> </tbody> </table>	Pin	Signal	Pin	Signal	1	GND	2	GND	3	GND	4	GND	5	GND	6	DEV_3V3	7	DEV_3V3	8	BUTTON_PWR_ON	9	FORCE_RECOVER Y					
Pin	Signal	Pin	Signal																									
1	GND	2	GND																									
3	GND	4	GND																									
5	GND	6	DEV_3V3																									
7	DEV_3V3	8	BUTTON_PWR_ON																									
9	FORCE_RECOVER Y																											

4.8 WIFI Antenna Connector

Function	Wifi antenna interface	
Marking	AT1 AT2	
Type	ipex to sma female	

5 Hardware update history

Z509-TX2 NX board hardware update history

Version	Update description
V2.0	Initial release

6 Product size diagram





7 Software/BSP Details

Z509-TX2 NX Smart Box is working on a system burned with the official original version of NVIDIA Linux For Tegra (L4T). HDMI, Gigabit Ethernet, USB2.0, serial port, GPIO, SD card, I2C bus can all be supported. But Mini-PCIe, USB3.0, fan interface, etc. cannot work normally.

Z509-TX2 NX smart box interface is fully supported, and the supporting driver patch needs to be loaded.

NVIDIA LT4 package can be downloaded from the following link

<https://developer.nvidia.com/embedded/linux-tegra>

Z509-TX2 NX patch support package download

<https://www.realtimesai.com>

Terms of Warranty

Important note

Each embedded product provided by Realtimes Technology is free from any defects in material and process,fully in line with the specifications officially issued by the original factory.

Realtimes Technology warranty covers the original products,If the parts configured by the dealer are out of order, please consult with the dealer to solve the problem. All the baseplate and core modules provided by Ruitai New Era (Beijing) Technology Co., Ltd. are guaranteed for 3 years, while the other peripherals are guaranteed for 1 year (life-long maintenance service is provided if the warranty period is beyond the warranty period). The warranty period starts from the date of delivery, for the products repaired within the warranty period, the repair parts shall be extended for 12 months.Unless notified by Realtimes Technology, the date of your original invoice shall be the date of shipment.

How do I get warranty services

If the product does not work properly, Please contact Realtimes Technology or dealer for warranty service, please show invoice when product warranty(this is the proof for you getting warranty service).

Warranty solution

When you ask for warranty service, please follow Realtimes Technology warranty process,You will need to receive your first diagnosis from a technical engineer by phone or by email,at that time,we need you to cooperate with us to fill in all the questions on the RMA form provided by us. Once we accurately determine the cause of the fault and the location of the damage ,we will provide the charge list for the out of warranty products,which needs your confirmation.Realtimes Technology keep the right to repair or replace the products. If the product is replaced or repaired, the replaced faulty product or the repaired and replaced faulty parts will be returned to Realtimes Technology.

For products under warranty,the customer shall bear the freight when the product is returned to the manufacturer,Realtimes Technology will bear the ship cost of the products after maintenance.

The following conditions are not covered by the warranty terms

- a) Improper installation, improper use, misuse and abuse of products(Overloading, for example).
- b) Improper maintenance and storage (Such as fire, explosion, etc) or natural disasters (such as lightning stroke,earthquake,typhoon,etc)
- c) Personal unauthorized changing the product(such as changing circuit characteristics, mechanical characteristics, software characteristics,Conformal coating).
- d) Other failures which are clearly due to misuse(such as overvoltage,polarity reversal, the pin bent or broken,the wrong connection,drop damage,transportation damage,damage due to over operating temperature and so on).
- e) The logo and part number on the product have been deleted or removed.
- f) The product is out of warranty.

Special concerns

If the same fault multiple occurrence for the products,in order to find out the reason causing the problem,we will request the users to provide the specific documents or information of peripheral equipment,such as monitor,I/O boards,cables,power supply, diagram and structure of the system,etc.If such documents or information are not available,we have the right to refuse to perform the warranty, the repairments will be charged accordingly.

Rev.C 6/2020